



SLS2 SERIES FREQUENCY SYNTHESIZER

0.010 GHz to 15 GHz (IN BANDS)
 Extended Bands to 20.0 GHz

SPECIFICATION	
Output frequency range capabilities	0.010 GHz to 15 GHz (In Bands)
Examples of standard frequency bands	1 GHz to 2 GHz 2 GHz to 4 GHz
(Contact factory for custom frequency bands)	3 GHz to 6 GHz 4 GHz to 8 GHz 9 GHz to 11 GHz 10.405 GHz to 11.450 GHz 11.450 GHz to 12.570 GHz 12.720 GHz to 14.840 GHz Multi-octaves also available
Step size	1 kHz (custom step sizes available)
Output power	+13 dBm minimum
Output power variation	± 2 dBm
Output harmonic in narrow band	-20 dBc maximum
Output harmonic in octave bandwidths	-15 dBc maximum
Subharmonics for 15 GHz to 19 GHz bands	-10 dBc maximum
Output spurious	-60 dBc maximum
Phase noise	See graph
Input reference frequency Standard 10 MHz custom	10 MHz (Custom reference frequencies available from 1 MHz to 200 MHz). Also available is programmable varying reference.
Input reference power level	0±3 dBm
Input impedance	50 ohms
Load VSWR	1.5:1 nominal
DC power requirements	+7 volts to +24 volts at 3.5 W typical, 4 W maximum Single rail supply
Phase lock alarm	TTL High in lock, low out of lock
Frequency control	Serial RS-422 (4 wire) or USB

PHASE NOISE SPECIFICATIONS (dBC/Hz), typical	OFFSET (Hz)						
	10	100	1K	10K	100K	300K	1M
12700 MHz	-42	-77	-94	-99	-100	-105	-116
14840 MHz	-42	-75	-92	-97	-98	-104	-115



L3Harris's SLS2 series of high spectral purity synthesizers offer a low price alternative for L, S, C and Ku-bands with the lowest phase noise. With standard 1 kHz step size output at all bands the SLS2 series synthesizers are ideal for dual conversion up and down converters. With +13 dBm output power and 60 dBc spurious suppression, the SLS2 series support the most stringent system applications. Consuming less than 4 Watt maximum from (+7 to 28 V) DC supply.

