MITEQ INC.

REVISIONS

ZONE	LTR	DESCRIPTION	DATE	APPROVED
	A	INITIAL RELEASE	8/26/2005	M. Hannon

STAMP P/N

SEE NOTE 3

DETAIL-A
(ROTATED 90° CCW)

.250 DIA

.233

NOTES:

1. MATERIAL: .090 THK. ALUMINUM ALLOY 5052-H5
2. FINISH: IRRIDITE CLASS I.
3. INSIDE RADIUS .095

HOLE SCHEDULE

HOLE	DESCRIPTION	QTY
A	SEE DETAIL-A	1
B	.166 +.003 -.000 DIA FOR 4-40-2 PEM NUT (FARSIDE)	2
C	.128 DIA C'SINK @ 82° TO .235 DIA (NEARSIDE)	2
D	.111 DIA C'SINK @ 82° TO .185 DIA (NEARSIDE)	2

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON
DECIMALS   ANGLES
.XX±.01   .XXX±.005   ±0°30'

MATERIAL

SEE NOTE 1

FINISH

SEE NOTE 2

HEAT TREAT

NEXT ASSY | USED ON

APPLICATION

| DRN BY | NAME M.Hannon | DATE 8/26/2005 |
| CHKD BY | M. Hannon | 9/8/2005 |

APPROVED BY

PROJ ENGR	W. Gardiner	9/9/2005
ENG SECT		
Q.A.		

MITEQ
100 Davids Drive, Hauppauge, New York 11788

RF TRAY

SIZE	CODE IDENT. NO.		REV.
B	33592	163743	A

SCALE | REF | SHEET 1 OF 1