



REVISIONS			
ZONE	LTR	DESCRIPTION	DATE APPROVED
1		INITIAL RELEASE	06/02/10

\* THESE FUNCTIONS ARE USED ONLY WITH FAULT ALARM OPTION

CONNECTOR PIN ASSIGNMENTS	
PIN	FUNCTION
A	+15VDC
B	GROUND
C	GROUND
D*	NORMALLY OPEN (FAULT)
E*	COMMON
F*	NORMALLY CLOSED (OPERATE)

DASH NO. TABLE			
DASH	DESCRIPTION	DIM "A"	DIM "B"
-1	STANARD LNA	2.30 [58.4]	2.49 [63.3]
-1	-F LNA W/ OPTIONAL FAULT ALARM	2.30 [58.4]	2.49 [63.3]
-2	-O LNA W/ OPTIONAL 100-240 VAC POWER SUPPLY	3.02 [76.7]	3.21 [81.5]
-2	-O -F LNA W/ OPTIONAL FAULT ALARM & 100-240 VAC POWER SUPPLY	3.02 [76.7]	3.21 [81.5]

- NOTES:  
 1. METRIC EQUIVALENTS ARE SHOWN IN BRACKETS.  
 2. MS3112E10-6P MATES WITH MS3116E10-6S.  
 3. CONTACT FACTORY FOR VARIOUS PINOUT CONFIGURATIONS.

-5	-4	-3	-2	-1	NOMENCLATURE OR DESCRIPTION	SYM/NOTES	PART NO.	CODE IDENT.	ITEM NO.
QTY REQ'D					PARTS LIST				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON					 100 Davids Drive, Hauppauge, New York 11788				
DECIMALS .XX±.01					DRW BY: NAME & Perno DATE 06/02/10 DRAFTING				
ANGLES .XXX±.005 ±0°30'					APPROVED BY: John Spaldinger 06/03/10				
MATERIAL					FINISH				
SIZE C					CODE IDENT. NO. 33592		195803		REV. 1
SCALE					REF		SHEET 1 OF 1		