MITEQ INC.

209779

		REVISIONS		
ZONE	LTR	DESCRIPTION	DATE	APPROVED
	D	Incorporate ECN 29562	11/20/13	RScherer

TOP VIEW

10.33 [262.26]

REAR

FRONT

EXHAUST

10.12 [256.92]

4.28 [108.74]

INTAKE

SIDE VIEW

NSP4044-S-NVG
40GHz to 44GHz
Variable Gain Amplifier
Gain = 40dBmn., N.F. 5.0dB max.

Attenuation
15dB

REMOTE
LOCAL

RF IN   RF OUT

CAUTION
+13 dBm CW MAX
NO DC VOLTAGE

ENT

POWER SWITCH

FRONT VIEW

FEMALE 2.4 mm
INPUT AND OUTPUT
CONNECTORS

INPUT: 100-240 VAC
50/60 Hz
FUSE
T 1.0 A / 250V

SN XXXXXX

CE

POWER INPUT
CABLE INCLUDED

GROUND TERMINAL

REAR VIEW

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON

DECIMALS	ANGLES
.XX±.01 .XXX±.005	±0°30'

MATERIAL

FINISH

NEXT ASSY   USED ON

APPLICATION

	NAME	DATE
DRN BY	RScherer	10/22/13
CHKD BY	RScherer	11/20/13
APPROVED BY		
PROJ ENGR	N. Shaikh	11/20/13
ENG SECT		
Q.A.		

MITEQ INC.®
100 Davids Drive, Hauppauge, New York 11788

NSP4044-S-NVG
OUTLINE

SIZE	CODE IDENT. NO.		REV.
B	33592	209779	D

DO NOT SCALE DRAWING

SCALE   REF   SHEET   1 OF 1